

# CATÁLOGO DE EQUIPOS DISPONIBLES EN UNISCAN



Referencia	No. Parte	Descripción
<b>LECTORES DE CÓDIGO DE BARRA</b>		
	ZEB-LS1203-7AZU0100S	Lector Laser 1D, incluye Stand, cable USB.
	ZEB-LI2208-SR7U2100S	Lector 1D, incluye Stand, cable USB.
	ZEB-DS2208-SR7U2100SGW	Imager 2D, Interface USB, IP42
	ZEB-DS2278-SR7U2100PRW	Lector inalámbrico Imager 2D, Incluye Cuna, USB
	ZEB-DS8108-SR7U2100SGW	Lector Zebra DS8108 - 1D/2D - Negro
	ZEB-DS8178-SR7U2100SFW	Lector inalámbrico 1D/2D
	ZEB-DS4608-SR7U2100SGW	USB KIT: DS4608-SR00007ZZWW SCANNER, CBA-U21-S07ZAR SHIELDED USB CABLE, 20-71043-04R STAND, BLACK
	ZEB-DS9308-SR4U2100AZW	Codificación 1D, 2D y PDF417, IP52, USB, RS232, cuña de teclado, TGCS (IBM) 46XX a través de RS485
	ZEBSP7201-SV4U2100ZCW	VERTICAL SP7201-SV Black Checkpoint EAS USB KIT: SP7201-SV00004ZCWW Scanner, CBA-U21-S07ZBR Shielded USB Cable
	SP7201-SH4U2100BGW	SP7201-SH Black Sapphire Glass, Checkpoint EAS, Bucket Mount USB KIT: SP7201-SH00004SCWW Scanner, CBA-U21-S07ZBR Shielded USB Cable, BRKT-BM0072-00 Bucket
	DS3678-ER3U42A2SVW	RUGGED GREEN VIBRATION MOTOR STANDARD CRADLE USB NO LINE CORD KIT: DS3678-ER2F003VZWW SCANNER, CBA-U42-S07PAR SHIELDED USB CABLE SUPPORTS 12V P/S, STB3678-C100F3WW CRADLE, PWR-BGA12V50W0WW P/S, CBL-DC-451A1-01 DC CBL
	DS3678-SR3U42A0SFW	Rugged Green Standard Cradle USB No Line Cord Kit: DS3678 Scanner, CBA U42-S07PAR Shielded USB Cable Supports 12V P/S, STB3678-C100F3WW Cradle, PWR-BGA12V50W0WW Power Supply and CBL-DC-451A1-01 DC Line Cord
	MP7201-MNSLN000NN	SCNR, MP7201: MEDIUM, SINGLE INTERVAL SCALE, SAPPHIRE GLASS, OIML

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.



# Honeywell

Referencia	No. Parte	Descripción
<b>LECTORES DE CÓDIGO DE BARRA</b>		
	HSM-1250G-2USB-1-N	USB Kit: 1D, black scanner (1250g-2), flex neck presentation stand (STND-15F03-009-4), USB Type A 3m coiled cable (CBL-500-300-C00) and documentation, assembled in Mexico, TAA compliant
	HSM-1200G-2USB-1	USB Kit: 1D, black scanner (1200g-2), rigid presentation stand (STND-19R02-002-4), USB Type A 3m coiled cable (CBL-500-300-C00) and documentation
	HSM-MK9540-32B41-6	MS9540 Voyager RS232 Black
	HSM-MK5145-31A38	MS5145 Eclipse USB, Black
	HSM-11960GSR-2USB-N	1960g USB Kit: General Purpose, 1D, PDF417, 2D, SR focus, Black, USB Type A 3m straight cable (CBL-500-300-S00), NA/MX Only
	HSM-STND-22F00-016-6	Stand: gray, 22cm (9´) height, flexible rod, large oval weighted base, Xenon Ultra cup
	HSM-1991ISR-3USB-5-N	USB Kit: Wireless. Ultra rugged/industrial. 1D, PDF417, 2D, SR focus, with vib. Red scanner (1991iSR-3), smart battery (BAT-SCN05), charge & comm base (CCB22-100BT-03N) USB Type A 3m straight, 5v host power cable (CBL-500-300-S00). Assembled in Mexico. Pdf417, 2D, Sr Focus, Red Scanner (1991iSR-3)
	HSM-STND-22F00-001-6	HONEYWELL, ACCESSORY, XENON 1900, STAND, GRAY, 22CM (9") HEIGHT, FLEXIBLE ROD, WEIGHTED BASE, XENON CUP
	HSM-1470G2D-2USB-1	USB kit: Omni-directional, 1D, PDF, 2D, black, scanner (1450g2D-2), flexible presentation stand (STND-15F03-009-4), USB Type A 1.5m straight cable (CBL-500-150-S00)
	HSM-1472G2D-2USB-5-N	HONEYWELL, VOYAGER XP 1472G, USB KIT, OMNI DIRECCIONAL, 1D, PDF, 2D, BLACK SCANNER, (1472G2D-2), CHARGE & COMUNICATION BASE (CCB01-010BT-V1N), USB TYPE A 3.0M STRAIGHT CABLE (CBL-500-300-S00)
	HSM-HF680-R1-1USB	GEN7 Hand-free scanner Kit, 2D, Black; 1.5m USB host cable (50152257-001), global SKU
	HSM-7980G-2USBA-0	USB Kit: 1D, PDF, 2D, USB Type A 3m (9.8´) straight cable (CBL-500-300-S00-04), US power supply
	HSM-7980G-2SERA-0-6	RS232 SCANNER KIT, 1D, PDF, 2D, 3M (9.8') STRAIGHT CABLE (CBL-000-300-S00-00), LEV 6 US PWR SUPPLY (PS-05-1000W-A-6)

# DATALOGIC

Referencia	No. Parte	Descripción
<b>LECTORES DE CÓDIGO DE BARRA</b>		
	DAT-QW2120-BKK1S	DATALOGIC ADC QUICKSCAN LITE IMAGER, BLACK, USB INTERFACE
	DAT-QW2520-BKK1S	DATALOGIC, QUICKSCAN QW2520, KIT, 2D IMAGER, USB INTERFACE, BLACK, INCLUDES SCANNER AND USB CABLE 90A052258, STAND STD-QW25-BK
	DAT-90A052044 DAT90A052065	CABLES USB QW2120
	DAT-GD4430-BKK1	GRYPHON I GD4430, KIT, USB, 2D IMAGER




\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.

	DAT-90A052258	Cable, USB, Type A, PVCW, Straight, 2M, Black
	DAT-M3511-010210-0064	Datalogic LA MAGELLAN 3510HSI SAPPHERE PLATTER DEFAULT CONFIG 1D/2D SCAN



Referencia	No. Parte	Descripción
<b>LECTORES DE CÓDIGO DE BARRA</b>		
	UNI-MS246	Lector de pistas 1, II y III, negro, USB. Garantía: 2 años.
	UNI-MS836-SUCB00-SG	Lector láser con cable USB y base para manos libres (HW decoder)
	UNI-MS838-2UCB0S-SG	MS838 2D, USB (with stand)
	UNI-MS838-2UBB0D-SG	Imager 2D, inalámbrico 2.4GHz, 100 metros, IP54
	UNI-MS852-OUBB0C-SG	MS852B Extra Long range, 2D, Cuna, Cable USB con protective case
	UNI-MS822-2UBU02-SG	MS822B, 2D SR Imager, Bluetooth Wireless, with cradle integrated with 2.4G Dongle and cable
	UNI-MS633-DUBU00-SG	MS633 Standard (SE4710) Ring Scanner, Battery, USB Cable.
	MS912-2UBB00-SG	2D Pocket Scanner, 2MB, with Bluetooth and USB charging cable. Warranty: 1 year.
	UNI-TS100-SUCB00-SG	2D Scanner, USB, Desktop
	UNI-RP902-43A8S0G	UHF RFID Reader, Wireless, Pocket, 902-928 MHz (N.America), UHF, AMS AS3993, America, USB+BT, 1M, 0 ports, Green Product.



# ZKTeco

Referencia	No. Parte	Descripción
<b>NUEVOS SCANNERS ZKTECO 1D / 2D</b>		
	ZK-B201C-KT	2d Barcode Qrcode Scanner Pixel Sensor: 640 X 480 Cmos Decoding Depth Of Field: 0-15cm Decoding Speed: 25cm/S Communication Mode: Usb' (Includes Zk-Bs Stand)
	ZK-B203S	2d wireless image barcode scanner with base dpi: 640 x 480 pixelsfield of view:horizontal: 41°; vertical: 31°decoding depth of field: 3-30cm(depends on barcode) battery: 2000mahcommunication mode: 2.4ghz wirelesswireless distance: 60m max
	ZK-B101C-KT	1D Laser Barcode Scanner Light Source: Visible laser diode, 650nm Decoding Depth of Field: 0-15cm Communication Mode: (Standard)USB Decoding Speed: 100 times/s
	ZK-B103C-KT	1D Wireless Laser Barcode Scanner Light Source: Visible laser diode, 650nm Decoding Depth of Field: 0-15cm Communication Mode: (Standard) 2.4GHz Decoding Speed: 100 times/s Wireless Distance: 150m Max. Battery: 1600mAh (stand included)
	ZK-B206	1D Wireless Laser Barcode Scanner Light Source: Visible laser diode, 650nm Decoding Depth of Field: 0-15cm Communication Mode: (Standard) 2.4GHz Decoding Speed: 100 times/s Wireless Distance: 150m Max. Battery: 1600mAh (stand included)





## Honeywell

Referencia	No. Parte	Descripción
<b>IMPRESORAS DE CÓDIGO DE BARRAS</b>		
	HSM-203-186-201	FUENTE DE PODER PARA PC42
	HSM-50125125-001FRE	Honeywell, Spare Part/Printhead, Pc42, Printhead(Z3), Wide Glaze, Asm
	50123301-002FRE	FRE,RIBBON ACCESSORIES, 0.5IN, TIANMA
	HSM-50120013-001FRE	PC42T LINERLESS PLATEN ROLLER
	HSM-PM42200002	203DPI, TABLETOP PRINTER Eng display Font, US Power Cord
	HSM-50126706-001FRE	PM42, Printhead, 203DPI
	HSM-PD43A0310001020	TT 203dpi, Colour display, Ethernet, US power cord

## CITIZEN

Referencia	No. Parte	Descripción
<b>IMPRESORAS DE CÓDIGO DE BARRA</b>		
	CT-CL-E321XUBNNA	Barcode Label TT 203 DPI,USB, LAN & Serial BK
	CT-CL-S700IINNU-HC	CL-S700 Typell, DT/TT, 203DPI, w/Rotary Cutter, Gray, industrial nylon

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.

Referencia	No. Parte	Descripción
<b>IMPRESORAS DE CÓDIGO DE BARRAS</b>		
	<b>GAIN-GI-2408TM EMPOWER</b>	<b>4.3" full-color LCD screen for intuitive and convenient settings.</b> Industrial Barcode printer/US plug. 400 MHz 32-bit ARM9 processor with 128 MB SDRAM, 128 MB Flash memory. High print speed up to 8 inches per second. Connectivity USB, RS232, Ethernet. <b>Connectivity Wi-Fi.</b> Print speed 203mm (8")/second. Label capacity up to 203mm (8")OD. Ribbon capacity 450m. Firmware emulates TSPL, EPL, ZPL, ZPL II, DPL. Free Windows driver and Bartender label design software
	<b>GAIN-GA-2408T</b>	Barcode printer/US Plug. 400 MHz 32-bit ARM9 processor with 128MB SDRAM, 128MB Flash memory. Internal Ethernet, USB 2.0 Hi-Speed(480Mbps), USB host support HID, RS-232. Optional Wi-Fi(802.11b/g/n), Bluetooth support Android and iPhone. Print speed 203mm (8")/second Label capacity up to 127mm (5")OD. Ribbon capacity 300m. Firmware emulates TSPL, EPL, ZPL, ZPL II, DPL. Free Windows driver and Bartender label design software
	<b>GAIN-GS-2406TE</b>	Internal Ethernet, USB 2.0 Hi-Speed(480Mbps), USB host support HID, RS-232, 4" Barcode printer TT plug. 4 Inch Desktop TT Barcode Printer GS-2406T. 400 MHz 32-bit ARM9 processor with 64MB SDRAM, 32MB Flash memory (128 MB Flash memory optional). USB 2.0 Hi-Speed (480Mbps), USB host support HID. Optional Wi-Fi(802.11b/g/n), Bluetooth support Android and iPhone. Print speed 152.4mm (6")/second. Label capacity up to 127mm (5")OD. Ribbon capacity 300m. Firmware emulates TSPL, EPL, ZPL, ZPL II, DPL. Free Windows driver and Bartender label design software
	<b>GAIN-GS-2208D</b>	2" Barcode printer DT/US Plug 400 MHz 32-bit ARM9 processor with 64 MB SDRAM, 32 MB Flash (128 MB Flash memory optional). Internal Ethernet, USB 2.0 Hi-Speed(480Mbps), USB host support HID. Optional Wi-Fi(802.11b/g/n) Bluetooth support Android and iPhone. Print speed 203mm (8")/second. Label capacity up to 127mm (5")OD. Firmware emulates TSPL, EPL, ZPL, ZPL II, DPL. Free Windows driver and Bartender label design software.

Referencia	No. Parte	Descripción
<b>IMPRESORAS DE CÓDIGO DE BARRA</b>		
	<b>TD2125N</b>	2.2" Desktop Printer, DT, 203dpi, 6ips, LAN/ Host-USB/ USB/ Ser
	<b>PA-TDU-001</b>	Touch Panel & LCD Display Kit for TD2 Printers
	<b>TD4210D</b>	4.3" Desktop Printer, DT, 203dpi, 5ips, USB/ Ser
	<b>TD4420TN</b>	4.3" Desktop Printer, TT, 203dpi, 6ips, LAN/ USB/ Host-USB/ Ser
	<b>TJ4021TN</b>	4.7" Titan Industrial Printer, TT, 203dpi, 10ips, Color Touch Panel, LAN/ USB/ Host-USB/ Ser

	TJ4420TN	4.5" Titan Industrial Printer, TT, 203dpi, 14ips, Color LCD, LAN/ USB/Dual Host-USB/ Ser
	TJ4020TN	4.7" Titan Industrial Printer, TT, 203dpi, 10ips, LED, LAN/ USB/ Host-USB/ Ser
	PJ822	200dpi, 8.5" Width, Thermal Printer with USB C Connectivity/Charging (Printer only)
	RJ2030	RuggedJet, Portable 2" Direct Thermal Receipt Printer w/Bluetooth, USB, LCD Display, Reflective Media Sensors, Tear, Battery, Belt Clip & 2 Year Premier Warranty
	RJ3230B	RuggedJet, Portable 3" Direct Thermal Receipt/Label Printer w/Bluetooth, MFi, USB Type C
	RJ4250WBL	Mobile 4" DT Printer w/USB, Wi-Fi, Bluetooth/MFi, NFC Pairing
	PTE-110	4.3" Desktop Printer, DT, 203dpi, 5ips, USB/ Ser
	PT-E310BTVP PT-E510VP PTE560BTVP	Impresión de hasta 24 mm, Conectividad Bluetooth y USB-C, Cortador automático dual
	PT-P950NW	Compatible con Wi-Fi, LAN, USB y serie, 360 dpi, 36 mm de ancho, Cortadora automática
<b>ACCESORIOS</b>		
	PA-RC-001	4PocketJet Rugged Roll Case with Decurling Mechanism: Easy drop in loading, holds standard 2.13" diameter rolls
	LB4640	PocketJet Carrying Pocket Case
	PA-FFC-810LHC	PocketJet Rugged Mountable Carrying Case for use with fanfolded paper.

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.




Referencia	No. Parte	Descripción
<b>IMPRESORAS DE CÓDIGO DE BARRAS DE ESCRITORIO E INDUSTRIALES</b>		
	ZEB-ZD22042-D01G00EZ	Direct Thermal Printer ZD220; Standard EZPL, 203 dpi, US Power Cord, USB
	ZEB-ZD22042-T01G00EZ	Thermal Transfer Printer (74M) ZD220; Standard EZPL, 203 dpi, US Power Cord, USB
	ZEB-ZD23042-D01G00EZ	IMPRESORA ZEBRA ZD230 Direct Thermal, Standard EZPL, 203 DPI, USB
	ZEB-ZD23042-301G00EZ	THERMAL TRANSFER PRINTER STANDARD 203 dpi (reemplazo GT800)
	ZEB-ZD23042-301C00EZ	THERMALTRANSFER, EPL AND ZPL, USB, ETHERNET 10/100
	ZEB-ZD23042-321G00EZ	THERMAL TRANSFER PRINTER STANDARD 203 DPI, CUTTER
	ZEB-ZD4A042-301M00EZ	ZEBRA AIT, PRINTER, ZD421, THERMAL TRANSFER PRINTER (74/300M), 203 DPI, USB, USB HOST, MODULAR CONNECTIVITY SLOT, BTLE5, US CORD, EZPL
	ZEB-ZD4A042-301W02EZ	Thermal Transfer Printer (74/300M) ZD421; 203 dpi, USB, USB Host, Modular Connectivity Slot, 802.11ac, BT4, ROW, US Cord, Swiss Font, EZPL
	ZEB-ZT23142-T01000FZ	TT Printer ZT230; 203 dpi, US Cord, Serial, USB, Ethernet
	ZEB-ZT23142-T21000FZ	TT Printer ZT230; 203 dpi, US Cord, Serial, USB, Cutter with Catch Tray
	ZEB-ZT41142-T010000Z	IMPRESORA ZEBRA ZT411, USB 2.0, RS-232 Serial, 10/100 Ethernet, Bluetooth 2.1, USB Host, EPL 3
	ZEB-ZT41142-T210000Z	IMPRESORA ZT411; 4", 203 dpi, US Cord, Serial, USB, 10/100 Ethernet, Bluetooth 2.1/MFi, USB Host, Cutter w/ Catch Tray, EZPL
	ZEB-ZT41142-T410000Z	TT Printer ZT411; 4", 203 dpi, US Cord, Serial, USB, 10/100 Ethernet, Bluetooth 4.1/MFi, USB Host, Peel w/ Full Rewind, EZPL
	ZEB-ZT42162-T010000Z	TT Printer ZT421; 6", 203 dpi, US Cord, Serial, USB, 10/100 Ethernet, Bluetooth 4.1/MFi, USB Host, EZPL
	ZEB-ZT61042-T010100Z	TT, ZT610; 4", 203 DPI, US CORD, SERIAL, USB, GIGABIT ETHERNET, BLUETOOTH 4.0,
	ZEB-ZT61042-T110100Z	TT, ZT610; 4", 203 DPI, US CORD, SERIAL, USB, GIGABIT ETHERNET, BLUETOOTH 4.0, CUTTER

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.













Referencia	No. Parte	Descripción
<b>EQUIPOS MÓVILES</b>		
	ZEB-KT-TC15-ROLATAM	TC15 KIT for LATAM Pantalla 6.5". Memoria 4G/64GB Flash Dual Sim Android 11 TC15 terminal, USB wall charger, US, EU and ARG plugs, USB cable
	WLMT0-T22B6ABC2-A6	TC22; WLAN, Wifi 6, SE4710, 6" Display, 6GB/64GB, 16MP RFC, 5MP FFC, 2-Pin Back I/O, Standard Battery, NFC, BT, USB-C, GMS, ROW
	WCMTB-T27B6ABC2-A6 TC27	WWAN, 5G, Wifi 6, SE4710, 6" Display, 6GB/64GB, 16MP RFC, 5MP FFC, 2-Pin Back I/O, Standard Battery, NFC, BT, USB-C, SIM & ESIM, GMS, ROW
	ZEB-TC530E-0T1E1B1000-A6	TC53E, LAN, 6.0" DISPLAY, WIFI 6E, 6GB RAM/64GB ROM, SE4720 IMAGER, 16MP RFC, 8MP FFC, WARM SWAP, 4680 MAH STANDARD BATTERY, GMS, ROW ONLY
	ET60AW-0SQAGS00A0-A6	ET60, Standard Touch Screen, 8/128 GB RAM/Flash, Android GMS, Standard Battery, ROW
	ET65AW-ESQAGS00A0-A6	ET65, Standard Touch Screen, 1 physical SIM and 1 eSIM, 8/128 GB RAM/Flash, Android GMS, Standard Battery, ROW
	MC3401-0G1M54SS-A6	MC34, LAN, WIFI 6E, Gun, Bluetooth, NFC, 4.0" Display, Vibrator, Android GMS, SE58 Imager, 6GB RAM / 64GB UFS, 47 Key, 7000mAh Standard Battery, Rest of World





## Honeywell

Referencia	No. Parte	Descripción
<b>EQUIPOS MÓVILES</b>		
	HSM-EDA5S-11AE64N21RK	EDA5s Android 11 with GMS, WWAN and WLAN, S0703 Imager, 2.0GHz 8 core, 4GB/64GB Memory, 13MP+5MP Cameras, Bluetooth 5.1, NFC, Battery 3060 mAh, USB Type C
	HSM-EDA52-11AE64N21RK	EDA52 (2PIN) Android 11 with GMS, WWAN & WLAN, S0703 Imager, 2.0GHz 8 core, 4GB/64GB Memory, 13MP+5MP Cameras, Bluetooth 5.0, NFC, Battery 4500 mAh, USB Type
	HSM-EDA51-SP	EDA51 SCREEN PROTECTOR
	HSM-EDA51-SH-1	Charging cradle for charging ScanPal EDA50/EDA50hc/ EDA51 terminal and battery. USA power cord. Compatible with scan handle, nido de carga.
	HSM-50141376-001	TPU, RUBBER BOOT EDA51
	HSM-EDA70-HB-R	EDA70/71 HomeBase Kit includes Dock, power Supply and Power Plugs for ROW, Recharging tablet.
	HSM-EDA70-BAT-EXT-1	Honeywell, "Latam Only", Accessory, Eda70, Eda71, Extended Battery, 8850 Mah
	HSM-EDA70-UC-R	Honeywell, Eda70, Snap-On Cup With Std Type A Connector. Supports Usb Client.



\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.



Referencia	No. Parte	Descripción
<b>CÓMPUTO MÓVIL</b>		
	UNI-EA520-NAGFUMDG	EA520, Octa-core, Android 11, GMS certified, 4GB/64GB, 2D scan engine (SE4710), BT, WiFi, 4G LITE (US), Camera, GPS, HF, NFC, with USB cable, battery, power adapter.
	EA660-NA6FRMDG	UNI-EA660-NA6FRMDG EA660, Rugged Smartphone, Android 13, 2D engine SE4710, WLAN 6E, BT, HF, NFC, 5MP front camera, 16MP rear camera, with battery, hand strap, USB cable, and adaptor (US)
	EA660-NANFRMDG	HT330, Android 12 GMS, 2D, BT, WIFI, 4G LTE, Camera, GPS, with Battery, USB Charging Cable, Hand Strap con Gyroscopio, Ecompass, Light & Proximity Sensor. No incluye power adapter (1010-900058G)
	UNI-HT330-QA62UM3G	Android 12 GMS, 2D, BT, WIFI, Camera, GPS, with Battery and USB Charging Cable. No incluye power adapter (1010-900058G)
	UNI-HT730-NAL1UMBG	HT730, Android 10, 4GB RAM / 64GB Flash, 2D Engine N6703, BT
	UNI-PA768-QANFRMDG	6.3", 6G/64G, 2D, Android 12, 2G/3G/4G/5G, WIFI6E(2.4GHz+5GHz+6GHz), Terminal w/ bumper+ Battery+ USB Cable+ QC Adapter+handstrap
	RT112-QA6FUMDG	Rugged tablet, 2D Scan Engine, Android 13, WiFi, BT, Camera, GPS, HF, NFC, with Battery, USB Charging Cable (no incluye power line cord cable 1550-905931G)
	RT112-QANFUMDG	Rugged tablet, 2D Scan Engine, Android 13, 5G WWAN, WiFi, BT, Camera, GPS, HF, NFC, with Battery, USB Charging Cable, and Adapter
	WD200P	Lightweight, ergonomic 3.1 wearable Android10 computer (GMS-certified) powered by a Qualcomm660 octa-core at 2.2GHz, with 3GB RAM, 32GB storage, and a 2,050mAh battery offering up to 11 hours use.
	UNI-SP320-0N50U1DG	BT Printer (ZPL), Battery 2700mAh, USB Cable, Power Adapter, Belt Clip, Thermal Paper.

Referencia	No. Parte	Descripción
<b>PUNTO DE VENTA ANDROID IMIN</b>		
	IMIN-SWIFT1-KT	SWIFT 1 NFC/ ANDROID 11/8-CORE/1.6GHZ/4GB+32GB/6.5"/4G/MICPHONE/SPEAKER + HANDSTRAP + PRINTER OR SCANNER Wi-Fi: 802.11 a/b/n/ac (2.4GHz/5GHz) Bluetooth 5.0, 2G/3G/4G LTE
	IMIN-SWIFT-1-PRINTER	MODULO ADICIONAL: 58MM PRINTER/POGO PIN
	IMIN-SWIFT-1-SCANNER	MODULO ADICIONAL: SWIFT1 TOTINFO SCANNER 1D/2D
	IMIN-SWIFT2 PRO:	Android 13 CPU: 8-Core, Quad*A73 and Quad*A53, 2.0GHz Memory: 4GB+32GB Display: 6.5", 1600*720 Touch screen, Communications: 4G, WiFi, GPS Bluetooth, NFC, Hardware:0.3MP FF+5MP AF, 7.6V 3350mAh detachable Battery, Speed printing up to 100mm/s, 58mm in width & 50mm in diameter.
	IMIN-1-1	SWAN 1/ ANDROID 11/4-CORE, 2.0GHZ/4GB+32GB/15.6"/FHD/SPEAKER/DP
	IMIN-SWAN1-DISPLAY	SWAN 1 DISPLAY NFC/10.1" SCREEN / TOUCH / DP WITH ADJUSTABLE SCREEN CONNECTOR INCLUDED
	IMIN-D3-504	D3-504/ ANDROID 11/4-CORE, 2.0GHZ/2GB+16GB/15.6"/FHD/SPEAKER
	IMIN-D3-505	OS: Android 11 CPU: 4-Core, Quad*Cortex-A55, 2.0GHz Memory: 2GB+16GB Display: 15.6" 1920x1080 FHD Touch screen+10.1" 800x1280 Communications: WiFi, Bluetooth
	IMIN-D4-504	D4-504/ ANDROID 11/4-CORE, 2.0GHZ/4GB+32GB/15.6"/FHD+10.1"/ 80MM PRINTER/SPEAKER
	IMIN-M2MAX	M2 MAX / ANDROID 11 GO/8-CORE, 1.8GHZ/4GB+16GB/8"/0.3MP/CAMERA/58MM PRINTER/7.4V 2600MAH/BATTERY/SPEAKER/DUAL NANO SIM M2 MAX LANDSCAPE BASE INCLUDED Wi-Fi: 802.11 a/b/n/ac (2.4GHz/5GHz) Bluetooth 5.0+, GPS/GSM/4G LTE
	IMIN-X1-201	X1-201/ BARCODE SCANNER/ LINUX/1.0GHZ/32M/BEEPER/0.3M/-CAMERA
	IMIN-FALCON-1	FALCON 1 ANDROID 11/8-CORE,2.0GHZ/2GB+16GB/10.1"+2.4"/4G/ 80MMPRINTER/CAMERA/4G
	IMIN-FALCON-1-NFC	FALCON 1 NFC ANDROID 11/8-CORE, 2.0GHZ/4GB+32GB/10.1"+2.4" /4G/80MMPRINTER/CAMERA /4G
	CRANE 1 16"	OS: Android 13 CPU: 8-Core, Dual*A78 and Hexa*A55, 2.2GHz Memory: 4GB+64GB Display: 16" 1920x1200 FHD Touch screen Communications: WiFi, Bluetooth Hardware: 3W Speaker, MEMS Microphone*2 Interface: Type-A*6, Type-C*1, Earphone *1, TF Card*1, RJ11*1,RJ12*1, RJ45*1, Pogo Pin*3 Power: DC 24V/2.5A
	IMIN-CRANE -1	IMIN-CRANE -1- MSR MSR/Pogo pin
	IMIN-CRANE-1-SCANNER	Totinf Scanner/Pogo pin
	CRANE 1 21.5"	OS: Android 13 CPU: 8-Core, Dual*A78 and Hexa*A55, 2.2GHz Memory: 4GB+64GB Display: 21.5" 1920x1080 FHD Touch screen Communications: WiFi, Bluetooth Hardware: 3W Speaker, MEMS Microphone*2 Interface: Type-A*6, Type-C*1, Earphone *1, TF Card*1, RJ11*1,RJ12*1, RJ45*1, Pogo Pin*4 Power: DC 24V/2.5A
	CRANE 1 27"	OS: Android 13 CPU: 8-Core, Dual*A78 and Hexa*A55, 2.2GHz Memory: 4GB+64GB Display: 27" 1920x1080 FHD Touch screen Communications: WiFi, Bluetooth Hardware: 3W Speaker, MEMS Microphone*2 Interface: Type-A*6, Type-C*1, Earphone *1, TF Card*1, RJ11*1,RJ12*1, RJ45*1, Pogo Pin*4 Power: DC 24V/2.5A
	CRANE 1 32"	OS: Android 13 CPU: 8-Core, Dual*A78 and Hexa*A55, 2.2GHz Memory: 8GB+128GB Display: 32" 1920x1200 FHD Touch screen Communications: WiFi, Bluetooth Hardware: 3W Speaker, MEMS Microphone*2 Interface: Type-A*6, Type-C*1, Earphone *1, TF Card*1, RJ11*1,RJ12*1, RJ45*1, Pogo Pin*4 Power: DC 24V/2.5A
	CRANE 1 16" Display	16" 1920x1200 FHD Touch screen Hardware: 1.8m type-C cable Interface: Type-C*1
	IMIN - RETAIL STAND	Base, Screen vesa mount*2, Printer+Scanner holder*1, POS machine holder*1










Referencia	No. Parte	Descripción
<b>PUNTO DE VENTA ANDROID IMIN</b>		
	IMIN-TP-808 HRPT	HPRT TP808 80mm Cubic Bluetooth Thermal Receipt Printer
	IMIN-CRANE-1-STATUS LIGHT	2 Color LED light/Pogo pin
	TABLE STAND	
	FLOOR STAND	





Referencia	No. Parte	Descripción
<b>IMPRESORAS TÉRMICAS Y EQUIPOS PUNTO DE VENTA</b>		
	ZK-P8008	80mm Thermal Printer with auto-cutter, Print speed: 300mm/s TPH: 100Km, Output: DC 24V/2.5A Interface: USB+RS232 Dimension: 190*145*145mm <b>10% DESCUENTO</b>
	ZK-P8001E	80mm Thermal Printer with auto-cutter, Print speed: 300mm/s TPH: 100Km, Output: DC 24V/2.5A Interface: USB+RS232+LAN Dimension: 190*145*145mm <b>10% DESCUENTO</b>
	ZK-P8011C	80mm Thermal Receipt Printer with auto-cutter Scene: Kitchen printer Function: Sound and light alarm Print speed: 300mm/s TPH: 150Km Output: DC 24V/2.5A Interface: USB+LAN+RS232 Dimension: 185*145*136mm
	ZK-P5803	58mm Thermal Receipt Printer Print speed: 90mm/s Output: DC 12V/3A Interface: USB (Standard) Communication: Bluetooth
	ZK-P5808	58mm Portable Thermal Receipt Printer Print speed: 70mm/s TPH: 100Km Output: DC 9V/1A Built-in battery: 7.4V/1500mAh Interface: USB+232 Support Bluetooth 4.0
	ZK-P8005	80mm Thermal Receipt Printer with auto-cutter Print speed: 230mm/s TPH: 100Km Output: DC 24V/2.5A Interface: USB+LAN Dimension: 192*145*133mm
<b>CAJÓN DE DINERO</b>		
	ZK-C0508	Casing: Steel construction with cold-pressed front Lock: 3 positions key lock, Cash Tray:5B8C(5 bill,8 coin) with adjustable dividers Dimensions:410W*415D*100H(mm) Port:RJ11 12V/24V

Referencia	No. Parte	Descripción
<b>MONITORES TOUCH DE 15", 17"</b>		
	ZK-D1504	15" TFT LCD panel 1024*768 Domestic capacitive Touch Screen, Folding Base, 12V 3A power supply, Projected Capacitive Screen (NO BISEL)
	ZK-D1704	17" TFT LCD panel 1280*1024 Domestic Resistive Touch Screen Folding Base, 12V 3A power supply, Projected Capacitive Screen

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.




Referencia	No. Parte	Descripción
<b>TERMINALES DE PUNTO DE VENTA / PC TOUCH SCREEN</b>		
	ZK-BIO750	<b>NUEVO</b> CPU: INTEL CORE I5-6200U QUAD-CORE 2.3GHZ DISPLAY: 15" HD LCD, 1024*768 TOUCH PANNEL: PROJECTED CAPACITIVE TOUCH PANNEL CUSTOMER DISPLAY: LED 8C HIGH-DIFINITION DIGITAL TUBE MEMORY: 8GB RAM (DDR4) 256GB SSD COLOUR: BLACK AND GRAY, WHITE (OPTIONAL) USB PORT: 4*USB3.0, 2*USB2.0 POWER SUPPLY: DC 12V 5A
	ZK-SC01TD-W0601	<b>NUEVO</b> CPU: INTEL CELERON J1900 QUAD-CORE @ 2GHZ DISPLAY: 15.6" HD LCD, 1024*768 TOUCH PANNEL: PROJECTED CAPACITIVE TOUCH PANNEL CUSTOMER DISPLAY: LED 8C HIGH-DIFINITION DIGITAL TUBE MEMORY: 8GB RAM (DDR3) 256GB SSD COLOUR: BLACK AND GRAY, USB PORT: 2*USB3.0, 4*USB2.0 POWER SUPPLY: DC 12V 5
	ZK-Bio510	15" all-in-one POS terminal, CPU: Intel Celeron J1900 2.0 GHz Quad-Core, Projected Capacitive Touch Display, RAM Upgrade 4G SSD: Upgrade 128G NO OS
	ZK-Bio550	15" all-in-one POS terminal, CPU: Intel Core i5-4210U 1.7Ghz, USB Port: 2*USB3.0 & 4*USB2.0 RAM Upgrade 4G, SSD: Upgrade 128G NO OS
	ZK-Bio610C	15" all-in-one POS terminal, CPU: Intel Celeron J1900 2.0 GHz Quad-Core Projected Capacitive Touch Display, RAM Upgrade 4G SSD: Upgrade 128G NO OS. Supports Rack VESA
	ZK-Bio950	ALL IN ONE BIOMETRIC SMART POS TERMINAL CPU: INTEL CORE I5-4210U 1.7GHZ, NO OS, DISPLAY: 15" TFT LCD, 1024*768 RESOLUTION TOUCH PANNEL: PROJECTED CAPACITIVE TOUCH DISPLAY RAM: 8G STORAGE: 128G SSD CUSTOMER DISPLAY: LED 8C HIGH-DIFINITION DIGITAL TUBE OS: SUPPORT: POS READY 7/WINDOWS EMBEDDED 8.1 INDUSTRY/WIN10 IOT ENTERPRISE USB PORT: 2*USB3.0 & 4*USB2.0 POWER SUPPLY: 12V DC 5A ADAPTER
	ZK-VFD01	Vacuum Fluorescent Display 2lines*20 Characters Interface: USB port
	ZK-PWR BIO 510	Cable y fuente de poder para el equipo ZK-Bio550
<b>PANTALLAS DIGITAL SIGNAGE</b>		
	ZK-DS32WC	32" Digital Signage
	ZK-DS43WC	43" Digital Signage

## ēlo

Referencia	No. Parte	Descripción
<b>MONITORES Y POS TOUCH</b>		
	ELO-E534869	1509L 15.6-inch wide LCD (LED Backlight) Desktop, WW, IntelliTouch (SAW) Singletouch, USB Controller, Clear, Bezel, VGA video interface, Black.
	ELO-E179069	1717L 17-inch LCD (LED Backlight) Desktop, Availability, IntelliTouch (SAW) Single-touch, USB & RS232 Controller, Clear, Zero-bezel, VGA video interface, Black.

Referencia	No. Parte	Descripción
<b>MONITORES Y POS TOUCH</b>		
	<b>ELO-E135925</b>	ELO E-SERIES 2, NO OS, 15.6-INCH WIDE, 1366X768 HD DISPLAY, CELERON, 4GB RAM, 128GB SSD, PROJECTED CAPACITIVE 10-TOUCH, CLEAR, ETHERNET, BLACK, STAND, WORLDWIDE
	<b>ELO-E441385</b>	NUEVO EloPOS System 15-inch wide, No OS, Core i3, 4GB RAM, 128GB SSD, Projected Capacitive 10-touch, Zero-Bezel, Clear, Black, I/O Hub Stand.
	<b>ELO-E351600</b>	21.5" LCD touchscreen monitor - 16:9 - 14 ms - 22" Class - TouchPro Projected Capacitive - 10 Point(s) Multi-touch Screen - 1920 x 1080 - Full HD - Thin Film Transistor (TFT) - 16.7 Million Colors - 3,000:1 - 250 Nit
	<b>ELO-E441193</b>	Elo, Elopos System, 15-Inch Wide, Win 10, Core i3, 4Gb Ram, 128Gb Ssd, Projected Capacitive 10-Touch, Zero-Beezel, Antiglare, Black, I/O Hub Stand



Referencia	No. Parte	Descripción
<b>LECTOR DE BANDA MAGNÉTICA</b>		
	<b>IDT-3321-12</b>	IDTECH lector de banda magnética serial T 1,2
	<b>IDT-IDMB334133B</b>	IDTECH lector de banda magnética USB T 1,2,3,
	<b>UNI-MS246</b>	UNITECH MSR,3TRK,USB W/KBD EMU



Referencia	No. Parte	Descripción
<b>IMPRESORAS Y CINTAS</b>		
	<b>EPS-C31CA85834</b>	TM-T88V-834 PARALELA USB TÉRMICA
	<b>EPS-C31CH51001</b>	TM-T20III USB + SERIAL
	<b>EPS-C31C515806</b>	TM-U220 (USB) MATRIZ, RECIBO NEGRA
	<b>EPS-PS180</b>	FUENTE DE PODER EPSON
	<b>EPS-ERC-38B</b>	CINTA EPSON TMU220



\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.

Referencia	No. Parte	Descripción
<b>TERMINALES DE PUNTO DE VENTA / PC TOUCH SCREEN</b>		
	LOG-LDX1000UP-BK	POLE DISPLAY, LDX1000, 9MM 2X20 USB PORT POWERED
	LOG-LV5000	USB 9.7" 2nd Display Non-Touch 1024x768, with Bracket
	LOG-811084	FUENTE DE PODER LR2000
	LOG-680014	FUENTE DE PODER PARA SB1015




Referencia	No. Parte	Descripción
<b>IMPRESORAS DE PUNTO DE VENTA MATRICIALES</b>		
	STA-SP712MC-GRAY	STAR MICRONICS SP700, MATRICIAL, NEGRA PARALELA
	STA-37999300	STAR MICRONCS SP700, MATRICIAL, NEGRA, USB, CORTADOR
	STA-39339810	STAR MICRONCS SP742, MATRICIAL AUTO-CUTTER BT iOS
<b>IMPRESORAS DE PUNTO DE VENTA TÉRMICAS</b>		
	STA-39652110	mC-Print2, Thermal, 2", Cutter, Ethernet (LAN), USB, CloudPRNT, Black, Ext PS Included NUEVO m Collection
	STA-39654110	mC-Print3, Thermal, 3", Cutter, Ethernet (LAN), USB, CloudPRNT, Black, Ext PS Included NUEVO m Collection
	STA-39472310	IMPRESORA POS, STAR MICRONCS TSP100, TERMICA, NEGRA USB
	STA-39464910	TSP143IIILAN GY US, THERMAL PRINTER, CUTTER, ETHERNET (LAN), GREY, INTERNAL
	STA-37479001	Spare part, Head unit TSP65li, TSP100lii
	STA-39465031	BSC10UD-24 GRY US, BSC-10, térmica, cortador automático, Interfaz dual: USB/serial, gris, cable USB, fuente de alimentación incluida
	STA-39465530	BSC10, Thermal, 250mm/sec, Cutter, LAN, Gray, Ext UPS included
<b>CAJÓN DE DINERO</b>		
	STA-37969520	Cajón de dinero Choice, negro, 16 An. x 16 Prof., control por impresora, 5 billetes/8 monedas, 2 ranuras para medios, cable incluido
<b>mPOP STAR MICRONICS (mCollection)</b>		
	STA-39650211	mPOP, Black, Integrated Printer & Cash Drawer, Universal Tablet Stand, Int PS
	STA-RC700B	CINTA PARA IMPRESORA SP700
	STA-PS60-24A	POWER SUPPLY FOR TSP 600, 800, 1000


# CITIZEN

Referencia	No. Parte	Descripción
<b>IMPRESORAS DE PUNTO DE VENTA</b>		
	CT-S310II-U-BK	Thermal POS, CT-S310II, USB & SER, BK
	CT-E351RSU-BK	Thermal POS, CT-E351, FRONT EXIT, SERIAL, USB, BLACK






Referencia	No. Parte	Descripción
<b>IMPRESORA PUNTO DE VENTA</b>		
	GAIN-GP-C80250I PLUS	Receipt printer DT. 203DPI, print speed 250mm/s, print width 64/72 mm, Internal Ethernet, USB 2.0 Hi-Speed(480Mbps), RS-232. Optional Wi-Fi(802.11b/g/n), Bluetooth support Android and iPhone. Compatible with ESC/POS commands



Referencia	No. Parte	Descripción
<b>IMPRESORAS DE PUNTO DE VENTA</b>		
	UNI-SP320-0N50UMDG	Impresora, BT, batería de 2700mAh, con cable USB-C, fuente de poder 5V/2A (US)








Referencia	No. Parte	Descripción
<b>LECTORES DE HUELLA, RELOJ DE ASISTENCIA, PANELES DE FIRMAS</b>		
	SEC-EA4-0085P	Secugen, Hamster Plus, finger print reader SDU03P USB Fingerprint sensor W/AUTO-ON smart capture ready for difficult fingerprints, removable weighted stand
	DP-50013-001-104	Digital Persona, U ARE U 4500, Reader, Fingerprint
	FUL-FS88H	FS88 PIV FULTRONIC FS88 PIV CERTIFIED USB DESKTOP






Referencia	No. Parte	Descripción
<b>ANTENAS AM / RF, DESACTIVADORES Y TAGS ZKTECO (NUEVO)</b>		
	ZK-EAS-AM10A/MASTER	TECHNOLOGY: AM, OPERATING VOLTAGE: AC(50~60HZ)110~220V, RATED POWER: <=15W, COLOR: WHITE, CENTER FREQUENCY: 58KHZ, WORKING MODE: MONO, DETECTION RANGE: 1-2.4M (DEPEND ON TAG), MATERIAL: ACRYLIC, DIMENSION : 1550X390X20 MM, PACKAGE DIMENSION: 1610*450*170MM, PACKAGE : 1PCS/CTN, WEIGHT: 22KG/CTN"
	ZK-EAS-AM10A/VICE	TECHNOLOGY : AM, OPERATING VOLTAGE:AC(50~60HZ)110~220V, RATED POWER: <=15W COLOR: WHITE, CENTER FREQUENCY :58KHZ, WORKING MODE:MONO, DETECTION RANGE:1-2.4M(DEPEND ON TAG), MATERIAL : ACRYLIC, DIMENSION :1550X390X20MM, PACKAGE DIMENSION: 1610*450*170MM, PACKAGE :1PCS/CTN , PACKAGE WEIGHT : 22KG/CTN"

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.




Referencia	No. Parte	Descripción
<b>ANTENAS AM / RF, DESACTIVADORES Y TAGS ZKTECO (NUEVO)</b>		
	ZK-EAS-H30	SMALL PENCIL, FREQUENCY: 58KHZ, COLOR: BLACK, MATERIAL:ABS+MAGNETIC BAR (25MM),UNLOCKING METHOD:MAGNETIC UNLOCK DIMENSION:46X13MM; PACKING: 1000PCS/CTN, CTN SIZE: 40X30X13CM,G.W:8KGS/CTN
	ZK-EAS-D886	AM Deactivator, Color: Grey Operating Voltage: AC(50~60hz)110~220V, Material:ABS plastic+PCB board, Ctn Size:74.5X34.5X21.5CM
	ZK-EAS-CDR	AM Soft Label, Frequency:58Khz, Color:White ,Material:PVC + Chip Dimension:45X11MM, Packing: 5000 pcs/ctn Size:54X30X23CM (barcode)
	ZK-EAS-H32C	Big Flat Pencil, Frequency: 58Khz, Color: White/Black/Gray, Material:ABS + Magnetic bar (50mm), Unlocking method: Magnetic unlock, Dimension:73X16mm, Packing: 1000pcs/ctn Size: 45X30X20CM, G.W:15kgs/ctn
	ZK-RF20M	OPERATING VOLTAGE:AC(50~60HZ)110~220V RATED POWER:≤15W CENTER FREQUENCY:8.2MHZ SCANNING FREQUENCY:160/170/180 WORKING MODE:TX+RX MOTHERBOARD:9500 DETECTION RANGE:0.9-2.4M(DEPEND ON TAG) MAIN MATERIAL:ALUMINEM ALLOY APPEARANCE SIZE:1520*440*40MM PACKING SIZE:1630*520*190MM PACKING UNIT:2PCS/CTN PACKING G.W.:15KGS/CTN
	ZK-EAS-AMTAG9	FREQUENCY: 58KHZ, MATERIAL: ABS PLASTIC+MAGNETS STICK, COLOR: GREY, DIMENSION: 36*30MM, TYPE: AM TAG, LANYARD LENGTH: 25CM, PACKING UNIT: 500PCS/CTN, CTN
	ZK-EAS-769B	RF Plastic Deactivator, Color:Black, Operating Voltage: AC(50~60hz)110~220V, Material:ABS plastic+PCB board, PAD Dimension:24.5X23.5CM, Hole Dimension: 21.5x20.5CM
	ZK-EAS-D01	Detacher Surface: Galvanization Dimension: 70.7*23MM Magnetic: 4500GS Packing: 100pcs/ctnCtn Size:42*17*37cm G.W:18.1KGS/CTN
	ZK-EAS-H22C	Bottle tag Frequency: 8.2MHZ COLOR:BLACK LOCK:THREE BALLS CLUTCH,STANDARD/SUPER DIMENSION: 50MM LANYARD LENGTH :20CM OR CUSTOMIZE PACKING: 500PCS/CTN CTN SIZE:48X32X33CM W:12.5KGS/CTN
	EAS-H01	Hard Tag, Small square Frequency: 8.2MHZ MATERIAL: ABS PLASTIC + COIL COLOR: BLACK/GREY OR CUSTOMIZE LOCK:- THREE BALLS CLUTCH, STANDARD/SUPER 1000pcs/cnt
	ZK-EAS-L404	RF Tag Label 40*40mm/ white (Box of 20 Rolls of 1000 Labels)

Referencia	No. Parte	Descripción
<b>ZKTECO CONTROL DE ACCESO Y ASISTENCIA</b>		
	ZK-LP400/ID	Fingerprint Capacity: 3000 /ID Card Capacity:10, 000 (Optional) /Record Capacity:100, 000
	ZK-MB10-VL/ID	Terminal inalámbrica de tiempo y asistencia. Reconocimiento facial, huellas y tarjeta. <b>OPCIÓN WIFI</b>
	ZK-SpeedFace-V4L	Palm Capacity: 800F02030288/Display: 4" LCD Color Touch Screen/Face Capacity: 800/Card Capacity: 1,000/Transaction Capacity: 150, 000/Memory: 512MB RAM / 512MB Flash <b>WIFI</b>
	ZK-SpeedFace-V5L	Display: 5" LCD Color Touch Screen, Face Capacity: 6,000(1:N), FingerPrint Capacity:6,000, Memory: 512M RAM / 8G ROM <b>WIFI</b>
	ZK-SpeedFace-V5L-TI	Facial Recognition and Thermal Imaging Terminal with Mask Detection Detection Time: ≤0.2s Measurement Distance: 30 – 120cm Display: 5" LCD Color Touch Screen <b>WIFI</b>

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.

Referencia	No. Parte	Descripción
<b>ZKTECO CONTROL DE ACCESO Y ASISTENCIA</b>		
	ZK-SLK20R	Desktop USB Enrollment device, support Win10/8/7, support USB only. PIV Single Finger Capture Device y PIV Mobile ID FAP20 FBI Certification
	ZK-uFace800 Plus	Face capacity: 3000/Fingerprint Capacity: 4000/Palm Capacity:3000 / Card Capacity:10,000 / Communication: TCP/IP, USB-Host, Wiegand Out, WiFi (Optional), 3G
	ZK-BAT-UFaceE800 Plus	
	ZK-TK4100D	ID Thin card 85.6*54*0.95mm Tarjeta de proximidad 125 Khz / Código oculto e impreso




<b>BIOTRACK / CHECKPOINT</b>		
Referencia	No. Parte	Descripción
<b>CONTROL DE ASISTENCIA Y ACCESO</b>		
	CM-TK4100-SN	CR80.30, White PVC, Blank with Serialization, with Chip: TK4100 (código de la tarjeta oculto).
	MF1ICS50-1K	Tarjeta de proximidad Mifare (1K) 13.56 Mhz
	CM-65BX Cardmark	Cr8030, Consumable, Pvc Card, White, Ppfl Gq, 3.375" X 2.125", 500 Card Per Sleeve

<b>TOPAZ SYSTEMS - PANELES DE FIRMA</b>		
Referencia	No. Parte	Descripción
<b>PANELES DE FIRMA</b>		
	TOP-T-LBK755SE-BHSB-R	TOPAZ, SIGNATURA GEM, TRANSACTION TERMINAL
	TOP-T-S460-HSB-R	TOPAZ, SIG LITE, TRANSACTION TERMINAL, SIG
	TOP-T-LBK462-HSB-R	TOPAZ, SIGNATUREGEM LCD 1X5 (HID USB BACKLIT),ELECTRONIC SIGNATURE PAD, WITH SOFTWARE, WITH 3 YEAR FACTORY WARRANTY




<b>UNISPOS</b>	
No. Parte	Descripción
<b>UNISPOS Antennas (8.2 Mhz), ETIQUETAS DE RF Y TAGS DE BOTELLAS</b>	
UNIS-AM04	Uniscan Pos RF Single EAS Aluminum Antenna with DSP
UNIS-DEA001	Uniscan Pos, RF Deactivator
UNIS-40X40R-B	RF Barcode Label 40*40mm (Box of 20 Rolls of 1000 Labels)
UNIS-40X40R-B-1	RF Barcode Label 40*40mm (1 Rolls of 1000 Labels)
UNIS-40X30RF-B	RF Barcode Label 40*30mm (Box of 20 Rolls of 1000 Labels)
UNIS-40X30RF-B-1	RF Barcode Label 40*30mm (1 Rolls of 1000 Labels)
UNIS-PWRS-AM04	Power Supply 1100v 60Hz for Single Antenna

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.


Referencia	No. Parte	Descripción
<b>IMPRESORAS ZC11, ZC31, ZC32 Y ALTA GAMA ZXP71/72/74 , ZXP9</b>		
	ZEB-ZC11-0000000LA00	Printer ZC100, Single Sided, Brazil Cord, USB Only
	ZEB-ZC11-0M00000LA00	Printer ZC100, Single Sided, US Cord, USB Only, ISO HiCo/LoCo Mag S/W Selectable
	ZEB-ZC11-0000Q00LA00	Printer ZC100, Single Sided, US Cord, USB Only, Windows Driver, CardStudio 2.0 (Standard) application,200 PVC cards, YMCKO ribbon (200 images)
	ZEB-ZC31-000C000LA00	Printer ZC300, Single Sided, US Cord, USB & Ethernet, Windows Driver
	ZEB-ZC31-0M0C000LA00	Printer ZC300, Single Sided, US Cord, USB & Ethernet, ISO HiCo/LoCo Mag S/W Selectable
	ZEB-ZC31-000CQ00LA00	Printer ZC300, Single Sided, US Cord, USB & Ethernet, Windows Driver, CardStudio 2.0 (Standard) application,200 PVC cards, YMCKO ribbon (200 images)
	ZEB-ZC32-000C000LA00	Printer ZC300, Dual Sided, US Cord, USB & Ethernet
	ZEB-ZC32-0M0C000LA00	Printer ZC300, Dual Sided, US Cord, USB & Ethernet, ISO HiCo/LoCo Mag S/W Selectable
	ZEB-ZC32-000CQ00LA00	Printer ZC300, Dual Sided, US Cord, USB & Ethernet, Windows Driver, CardStudio 2.0 (Standard) application, 200 PVC cards, YMCKOK ribbon (200 images)
	ZEB-Z71-000C0000US00	Zebra ZXP Series 7 Single-Sided Card Printer, USB and Ethernet Connectivity, US
	ZEB-Z71-0M0C0000US00	Zebra ZXP Series 7 Single-Sided Card Printer, Magnetic Encoder, USB and Ethernet
	ZEB-Z72-000C0000US00	Zebra ZXP Series 7 Dual-Sided Card Printer, USB and Ethernet Connectivity, US
	ZEB-Z72-0M0C0000US00	Zebra ZXP Series 7 Dual-Sided Card Printer, Magnetic Encoder, USB and Ethernet
	ZEB-Z74-000C0000US00	Zebra ZXP Series 7 Dual-Sided Card Printer and Dual-Sided Laminator, USB and Ethernet
	ZEB-Z74-0M0C0000US00	Zebra ZXP Series 7 Dual-Sided Card Printer and Dual-Sided Laminator, Magnetic, USB and Ethernet

Referencia	No. Parte	Descripción
<b>IMPRESORAS ZEBRA MOVILES: ZQ510, ZQ310 ZQ320, ZQ600</b>		
	ZEB-ZQ31-A0E04TL-00†	DT Printer ZQ310 Plus; Bluetooth 4.X, No Label Sensor, Outdoor Use, English, Group L
	ZEB-ZQ32-A0E04TL-00	DT Printer ZQ320 Plus; Bluetooth 4.X, No Label Sensor, Outdoor Use, English, Group L &nbsp;
	ZEB-ZQ51-BUW000L-00	DT Printer ZQ511, media width 3.15"/80mm; English/Latin fonts, 802.11ac/Bluetooth 4.1, stdn battery, Latin American certs




Referencia	No. Parte	Descripción
<b>IMPRESORAS ZEBRA MOVILES: ZQ510, ZQ310 ZQ320, ZQ600</b>		
	ZEB-ZQ51-BUE000L-00	DT Printer ZQ511 media width 3.15"/80mm; English/Latin fonts, Bluetooth 4.1, stnd battery, Latin American certs
	ZEB-ZQ52-BUW000L-00	DT Printer ZQ521, media width 4.45"/113mm; English/Latin fonts, 802.11ac/Bluetooth 4.1, stnd battery, Latin American certs
	ZEB-ZQ52-BUE000L-00	DT Printer ZQ521 media width 4.45"/113mm; English/Latin fonts, Bluetooth 4.1, stnd battery, Latin American certs
	ZEB-ZQ61-AUFAL04-00	DT Printer ZQ610 Plus 2"/48mm; English/Latin fonts,BT 4.x, Lined platen, 0.75" core, Group L, Belt clip
	ZEB-ZQ61-AUWA004-00	DT Printer ZQ610 Plus 2"/48mm;English/Latin fonts,ZPL ,802.11AC /BT4.X,DT/Lined Platen, 0.75" Core,English,Grouping 0,Belt Clip
	ZEB-ZQ62-AUWAL04-00	DT Printer ZQ620 Plus 3"/72mm; English fonts,Dual 802.11AC / BT4.x, Lined platen, 0.75" core, Group L, Belt clip
	ZEB-ZQ63-AUWA004-00	DT Printer ZQ630 Plus; English fonts,Dual 802.11AC / BT4.x, Lined platen, 0.75" core, Group 0, Belt clip



## Honeywell

Referencia	No. Parte	Descripción
<b>IMPRESORAS HONEYWELL PORTÁTILES</b>		
	HSM-MPD31D112	3" MOBILE PRINTER, US AC






Referencia	No. Parte	Descripción
<b>IMPRESORAS STAR PORTÁTILES</b>		
	STA-39633200	Star Micronics, Mobile Printer, SM-L300-UB57, SM-L300, Portable Thermal 3", Receipt/Restick/Label, Tear Bar, Bluetooth3.0/BLE/USB, Black, No MSR, Belt Clip/Battery/USB cable included, USB AC adapter needed





Referencia	No. Parte	Descripción
<b>MONITORES AUTOCONSULTA</b>		
	E461790 (Price chek)	Elo I-Series 3.0 STANDARD, Android 8.1 with Google Play Services, 10.1-inch, HD 1280 x 800 display, ARM A53 2.0 GHz Octa-Core Processor, 3GB RAM, 32GB Flash, PCAP 10-touch, Clear, Wi-Fi, Ethernet, Bluetooth 4.1, EloView, compatible, Black, Worldwide.
	E462589	Elo I-Series 3.0 STANDARD, Android 8.1 with Google Play Services, 21.5-inch Full HD 1920 x 1080 IPS display, ARM A53 2.0 GHz Octa-Core Processor, 3GB RAM, 32GB Flash. PCAP 10-touch, Clear, Wi-Fi, Ethernet, Bluetooth 4.1, EloView compatible, Black, Worldwide.




Referencia	No. Parte	Descripción
<b>MONITORES AUTOCONSULTA</b>		
	E850387	Elo I-Series 2.0, No OS, 21.5-inch wide, Full HD 1920 x 1080 display, Core i3, 8GB RAM, 128GB SSD, Projected Capacitive 10-touch, Clear, Wi-Fi, Ethernet, Bluetooth 5.0, Black, Worldwide.
	E926356	Lector de Código de Barras ELO-KIT, 2DBCR, USB, N3680 / , 2D, (based on the N3680 engine) for I-Series (Android and Windows), X-Series -02 Series Monitors and -02 Series IDS.
	E796965	Wallaby self-service floor stand top. Supports Epson or Star printers and 15-inch or 22-inch I-Series (Note: complete self-service floor stand requires floor base part E797162 sold separately).
	E797162	Wallaby self-service floor base (requires floor top E796965 for complete self-service floor stand).
	E143088	KIT,WALL MOUNT, ESYxx EX-Series / Wall mount for E-/I-/X-Series Intel/Windows based all-in-one touch computers






Referencia	No. Parte	Descripción
<b>KIOSKOS, CONSULTA DE PRECIOS</b>		
	CC6000-10-3200LCWW	NG Concierge, 10 inch, Android OS, 32GB, Landscape, Imager, WW config
	CBL-DC-383A1-01	DC Line Cord for Running Single Slot Cradles or Charging Cables
	PWR-BUA5V16W0WW	Level VI AC/DC Power Supply Brick AC Input
	50-16000-182R	AC Line Cord, 6ft. (1.8m) Un-Grounded, Two Wire.
	CC600-5-3200LNWW	NG Concierge, 5 inch, Android OS, 32GB, Ethernet/WIFI, Imager, WW config












Referencia	No. Parte	Descripción
<b>IMPRESORAS TÉRMICAS DE KIOSKO</b>		
	STA-IFBDHC04	Tarjeta de interfase paralela
	STA-39607910	Tarjeta de interfase USB
	STA-PS60-24A	Power supply for TSP 600, 800, 1000
	STA-37963774	SK1, KIOSK 3", PRESENTER, USB/SERIAL, EXT PS NEEDED
	STA-37963360	CB-SK1-D3 POWER CABLE, SK1, POWER CABLE ADAPTER TO PS-60 POWER SUPPLY, NCMR
	STA-30782110	PS60A-24C US, UNIVERSAL 24VDC OUTPUT POWER SUPPLY

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.



Referencia	No. Parte	Descripción
<b>NUEVO ZD510 BRAZALETES ZEBRA</b>		
	ZEB-ZD51013-D01E00FZ	NUEVA ZD510ZPL II, XML, 300 dpi, US Cord, USB, USB Host, Ethernet, BTLE
	ZEB- P1100266-003	300dpi Printhead for the ZD510 Healthcare Wristband Printer
	ZEB- P1100266-008	Platen Roller 300dpi Healthcar
Referencia	No. Parte	Descripción
<b>IMPRESORAS RFID</b>		
	ZEB-ZD6A142-301FR2EZ	Thermal Transfer Printer (74/300M) ZD621R, Color Touch LCD; 203 dpi, USB, USB Host, Ethernet, Serial, BTLE5, ROW, RFID - UHF, US Cord, Swiss Font, EZPL
<b>ETIQUETAS DE RFID</b>		
	ZEB-10038996	Label, Paper, 4x6in (101.6x152.4mm); TT, Z-Perform 1500T, Coated, Permanent Adhesive, 3in (76.2mm) core, RFID, Plain 1000ETXROLL
	ZEB-10039002	Label, Paper, 4x6in (101.6x152.4mm); TT, Z-Perform 1500T, Coated, Permanent Adhesive, 3in (76.2mm) core, RFID, Plain 200 ETXROLL
	ZEB-10039001	Label, Paper, 4x2in (101.6x50.8mm); TT, Z-Perform 1500T, Coated, Permanent Adhesive, 3in (76.2mm) core, RFID, Plain 1500XROLL
	ZEB-10039017	Label, Paper, 4x2in (101.6x50.8mm); TT, Z-Perform 1500T, Coated, Permanent Adhesive, 3in (76.2mm) core, RFID, Plain 500ETXROLL
<b>LECTORES, ANTENAS Y ACCESORIOS RFID</b>		
	ZEB-FX7500-42320A50-US	Radio, FX7500:RFID reader,4 port, GEN2, US
	ZEB-FX9600-42320A50-US	FX9600 Fixed RFID Reader - 4-PORT, POE, US only
	ZEB-PWR-BGA24V78W1WW	Power supply, Fixed RFID Reader, DC Cable included, -20C TO +55C
	ZEB-AN480-CL66100WR	AN480 Antenna: 1 Port, General Purpose, Wide-Band-Left, Pig-Tail, Left-Hand Circular Polarization, RoHS. (Worldwide)
	ZEB-AN480-CR66100WR	AN480 Antenna: 1 Port, General Purpose, Wide-Band-Right, Pig-Tail, Right Hand Circular Polarization, RoHS. (Worldwide)
	ZEB-CBLRD-1B4002400R	RF Cable 240" ; Cable Type LMR 240
	ZEB-CBLRD-1B4001800R	RF Cable 180" ; Cable Type LMR 240
	ZEB-CBLRD-1B4000680R	RF Cable 68" ; Cable Type LMR 240
	ZEB-BRKT-70661-01R - KIT	Standard Mount for AN400 and AN480 Antenna
	ZEB-BRKT-70662-01R - KIT	Heavy Duty 16? Mount Bracket for AN400 and AN480 Antenna

Referencia	No. Parte	Descripción
<b>EQUIPOS MOVILES RFID</b>		
   	RFD4031-G00B700-WR	RFD40, Premium, Standard Range Circular Polarized Antenna, UHF RFID, Bluetooth, WiFi, Gun, No Imager, 7000mAh Battery, Midnight Black, 900MHz Worldwideattery, ROW
	CBL-DC-388A1-01 DC	Line Cord for running the single slot cradles or battery chargers
	23844-00-00R	AC Line Cord, 7.5 feet long, grounded, three wire. Associated Country: US
	ADP-RFD40-TC2X-2R	Sleded adapter with Bluetooth communication allows TC22 / TC27; HC20 / HC50 devices to be mounted on top of RFD40.D40.
	CR40-1S0T-TC2-G-02	RFD40 Device Slot/0 Toaster Slots, Charge Only Cradle with support for TC22/27 & HC20/50.
	PWR-BGA12V50W0WW	Level VI efficiency AC / DC power supply brick used to power single-slot cradle or four-slot battery charger.

Referencia	No. Parte	Descripción
<b>LECTORES Y EQUIPOS MOVILES RFID</b>		
	UNI-RP902-43A8S0G	UHF RFID Reader, Wireless, Pocket, 902-928 MHz (N.America), UHF, AMS AS3993, America, USB+BT, 1M, 0 ports, Green Product.
	UNI-HT730-ZA66UMBG	HT730UHF, Android 10 with GMS, 2D engine, RFID UHF (US antenna, 902-928MHz), BT, WiFi, Camera, with 38-key keypad, with battery and hand strap (Charging Accessories Not Included)
<b>ANTENAS RFID</b>		
  	UNI-RS200-75G5S2G	RFID Reader_865-928 MHz (Global UHF)_M6e Micro / Non_Global_USB + UART_Stationary Standard_Two ports_Greenmicro USB, Terminal block.
	UNI-4060-900011G	RS200 8dBi Antenna for US 902-928MHz (replace 205367G)
	UNI-1550-900102G	RS200 3m SMA RF cable
	UNI-1010-900007G	Input: 100~240V, Output:12V 2A, Switching adapter
	UNI-1010-601551G	Power Cord

\*Imágenes referenciales

\*Consulte precios, disponibilidad y promociones con su asesor comercial asignado.

\*Consulte suministros y accesorios con su asesor asignado.

\*Este catálogo se actualiza constantemente, favor revisar la fecha de edición ubicada al inicio y final del mismo.